

KOGA Signature Geometry WorldTraveller-S & GrandTourer-S - 2017

SIZE	Seattube		Toptube		Chainstay		Wheelbase		BB-Drop		Rake		HT Angle	ST Angle	Trail		Headtube		Reach		Stack	
	Center-Top		T/T Effective		C/S										H/T							
	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	degr	degr	mm	Inches	mm	Inches	mm	Inches	mm	Inches

WorldTraveller-S

50	500	19,69	570	22,44	470	18,50	1105	43,50	60	2,36	50	1,97	70,0	73,5	76	2,99	115	4,53	405	15,94	556	21,89
54	540	21,26	580	22,83	470	18,50	1116	43,94	60	2,36	50	1,97	70,0	73,5	76	2,99	130	5,12	411	16,18	570	22,44
57	570	22,44	601	23,66	470	18,50	1127	44,37	60	2,36	50	1,97	70,5	73,0	73	2,87	150	5,91	420	16,54	591	23,27
60	600	23,62	604	23,78	470	18,50	1125	44,29	60	2,36	50	1,97	70,5	72,5	73	2,87	170	6,69	412	16,22	610	24,02
63	630	24,80	620	24,41	470	18,50	1130	44,49	60	2,36	50	1,97	71,0	72,0	70	2,76	200	7,87	413	16,26	640	25,20

WorldTraveller-S Mixed

47	470	18,50	566	22,28	470	18,50	1103	43,43	60	2,36	50	1,97	70,0	73,5	76	2,99	150	5,91	392	15,43	589	23,19
50	500	19,69	574	22,60	470	18,50	1112	43,78	60	2,36	50	1,97	70,0	73,5	76	2,99	160	6,30	397	15,63	598	23,54
53	530	20,87	583	22,95	470	18,50	1110	43,70	60	2,36	50	1,97	70,5	73,0	73	2,87	170	6,69	394	15,51	607	23,90
56	560	22,05	590	23,23	470	18,50	1118	44,02	60	2,36	50	1,97	70,5	73,0	73	2,87	180	7,09	401	15,79	619	24,37
59	590	23,23	600	23,62	470	18,50	1117	43,98	60	2,36	50	1,97	71,0	72,5	70	2,76	190	7,48	401	15,79	631	24,84

GrandTourer-S

50	500	19,69	570	22,44	460	18,11	1077	42,40	55	2,17	45	1,77	70,0	72,0	75	2,95	120	4,72	382	15,04	581	22,87
54	540	21,26	574	22,60	460	18,11	1081	42,56	55	2,17	45	1,77	70,0	72,0	75	2,95	135	5,31	381	15,00	595	23,43
57	570	22,44	601	23,66	460	18,11	1087	42,80	55	2,17	45	1,77	71,0	71,0	68	2,68	150	5,91	390	15,35	613	24,13
60	600	23,62	604	23,78	460	18,11	1090	42,91	55	2,17	45	1,77	71,0	71,0	68	2,68	165	6,50	388	15,28	627	24,69
63	630	24,80	620	24,41	460	18,11	1092	42,99	55	2,17	45	1,77	71,0	70,0	68	2,68	205	8,07	378	14,88	665	26,18

GrandTourer-S Low Entry

47	470	18,50	567	22,32	460	18,11	1076	42,36	55	2,17	45	1,77	70,0	72,0	75	2,95	160	6,30	366	14,41	618	24,33
50	500	19,69	567	22,32	460	18,11	1076	42,36	55	2,17	45	1,77	70,0	72,0	75	2,95	170	6,69	363	14,29	628	24,72
53	530	20,87	571	22,48	460	18,11	1080	42,52	55	2,17	45	1,77	70,0	72,0	75	2,95	180	7,09	364	14,33	637	25,08
56	560	22,05	599	23,58	460	18,11	1085	42,72	55	2,17	45	1,77	71,0	71,0	68	2,68	190	7,48	375	14,76	651	25,63
59	590	23,23	604	23,78	460	18,11	1090	42,91	55	2,17	45	1,77	71,0	71,0	68	2,68	200	7,87	377	14,84	660	25,98

